

Model		RW-F10.2-B
Main Parameter		
Battery Chemistry		LiFePO ₄
Built-in Circuit Breaker		125A 4P, 60Vdc
Capacity (Ah)		200
Scalability		Max. 32 pcs pack (Max.327kWh) in parallel
Nominal Voltage (V)		51.2
Operating Voltage (V)		43.2 ~ 57.6
Nominal Energy (kWh)		10.24
Usable Energy (kWh) ^[1]		9.2
Charge / Discharge Current (A) ^[2]	Recommend Continuous	Charge : 100 / Discharge : 100
	Max. Continuous	Charge : 198 / Discharge : 240
	Peak (2mins, 25°C)	300
Other Parameter		
Recommend Depth of Discharge		90%
Dimension (W × H × D)		23.6" × 32.7" × 7.9" (600 × 830 × 200mm, Without hanging board)
Weight Approximate		235.9 lbs. (107kg)
Master LED Indicator		LED (SOC : 20% ~ SOC100% and working state)
IP Rating of Enclosure		NEMA 3R (IP65)
Operating Temperature		Charge : 33°F ~ 131°F (1 ~ 55°C) / Discharge : -4°F ~ 131°F (-20°C ~ 55°C)
Recommend Operating Temperature		59°F ~ 95°F (15°C ~ 35°C)
Storage Temperature		32°F ~ 95°F (0 ~ 35°C)
External ambient temperature range		-4°F ~ 131°F (-20°C ~ 55°C, with heating film)
Humidity		5% ~ 95%
Altitude		≤ Max. 9,843 ft (3,000m)
Cycle Life		≥6000 (25°C ± 2°C, 0.5C / 0.5C, 90%DOD, 70%EOL)
Installation		Wall-Mounted, Floor-Mounted
Communication Port		CAN2.0, RS485
Warranty Period ^[3]		10 years
Energy Throughput		32MWh (@25°C, 0.5C / 0.5C, 70%EOL)
Certification		UN38.3, FCC, UL1973, UL9540A

[1] DC Usable Energy, test conditions : 90% DOD, 0.5C charge & discharge at 25°C. System usable energy may vary due to system configuration parameters.

[2] The current is affected by temperature and SOC.

[3] Conditions apply, refer to Deye Warranty Letter.